

## DS-2CD1043G0-I 4.0 MP IR Network Bullet Camera



### Key Features

- 1/3" progressive scan CMOS
- 2560 × 1440@20fps
- 2.8 mm/4 mm/6 mm fixed lens
- H.265+, H.265, H.264+, H.264
- Dual stream
- 120 dB WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- Up to 30 m IR range
- PoE (Power over Ethernet)
- IP67



| <b>Camera</b>   |  |
|---|--|
| Image Sensor  | 1/3" progressive scan CMOS   |
| Min. Illumination   | Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON)  |
| Shutter Speed   | 1/3 s to 1/100, 000 s  |
| Slow Shutter  | Yes  |
| Auto-Iris   | No   |
| Day & Night   | IR cut filter  |
| DNR (Digital Noise Reduction)   | 3D DNR   |
| WDR (Wide Dynamic Range)  | 120 dB   |
| Angle Adjustment (Bracket)  | Pan: 0° to 360°, tilt: 0° to 180°, rotation: 0° to 360°  |
| <b>Lens</b>   |  |
| Focal Length  | 2.8 mm, 4 mm, 6 mm   |
| Aperture  | F2.0   |
| Focus   | No   |
| FOV   | 2.8 mm, horizontal FOV 100°, vertical FOV 55°, diagonal FOV 117°<br>4 mm, horizontal FOV 77°, vertical FOV 42°, diagonal FOV 88°<br>6 mm, horizontal FOV 51°, vertical FOV 28°, diagonal FOV 58° |
| Lens Mount  | M12  |
| <b>IR</b>   |  |
| IR Range  | Up to 30 m   |
| Wavelength  | 850 nm   |
| <b>Compression Standard</b>   |  |
| Video Compression   | Main stream: H.265/H.264<br>Sub stream: H.265/H.264/MJPEG  |
| H.264 Type  | Baseline Profile/Main Profile/High Profile   |
| H.264+  | Main stream supports   |
| H.265 Type  | Main Profile   |
| H.265+  | Main stream supports   |
| Video Bit Rate  | 32 Kbps to 8 Mbps  |
| <b>Smart Feature-set</b>  |  |
| Region of Interest  | 1 fixed region for main stream and sub-stream  |
| <b>Image</b>  |  |
| Max. Resolution   | 2560 × 1440  |
| Main Stream<br>Max. Frame Rate  | 50Hz: 20fps (2560 × 1440), 25fps (2304 × 1296, 1920 × 1080, 1280 × 720)<br>60Hz: 20fps (2560 × 1440), 30fps (2304 × 1296, 1920 × 1080, 1280 × 720)   |
| Sub-stream<br>Max. Frame Rate   | 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)<br>60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)   |
| Image Enhancement   | BLC, 3D DNR  |
| Image Settings  | Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser   |
| Day/Night Switch  | Auto, scheduled  |
| * Note: The frame rate of the sub-stream cannot exceed the maximum frame rate of the current main stream. |  |
| <b>Network</b>  |  |
| Network Storage   | NAS (NFS, SMB/CIFS)  |
| Alarm Trigger   | Motion detection, video tampering alarm, illegal login   |
| Protocols   | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6 UDP, Bonjour   |

|                               |   |
|-------------------------------|---|
| General Function              | Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter        |
| Firmware Version              | 5.5.3   |
| API                           | ONVIF (PROFILE S, PROFILE G), ISAPI   |
| Simultaneous Live View        | Up to 6 channels  |
| User/Host                     | Up to 32 users<br>3 levels: Administrator, Operator, and User   |
| Client                        | iVMS-4200, Hik-Connect, iVMS-5200   |
| Web Browser                   | IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+  |
| <b>Interface</b>              |   |
| Communication Interface       | 1 RJ45 10M/100M self-adaptive Ethernet port   |
| <b>General</b>                |   |
| Operating Conditions          | -30 °C to 50 °C (-22 °F to 122 °F), humidity: 95% or less (non-condensing)                              |
| Power Supply                  | 12 VDC ± 25%, 5.5 mm coaxial power plug<br>PoE (802.3af, class 3)                                       |
| Power Consumption and Current | 12 VDC, 0.4 A, Max: 5 W<br>PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.13 A, Max: 7 W                      |
| Protection Level              | IP67<br>TVS 2000V lightning protection, surge protection and voltage transient protection               |
| Material                      | Metal & Plastic   |
| Dimensions                    | Camera: Ø 70 mm × 172.7mm ( 2.7" × 6.8")<br>With package: 216 mm × 121 mm × 118 mm (8.5" × 4.8" × 4.6") |
| Weight                        | Camera: approx. 280 g (0.62 lb.)<br>With package: approx: 530 g (1.17 lb.)                              |

### Available Models

DS-2CD1043G0-I (2.8 mm), DS-2CD1043G0-I (4 mm), DS-2CD1043G0-I (6 mm)

### Typical Application


Hikvision products are classified into three levels according to their anti-corrosion performance. Refer to the following description to choose for your using environment.

This model has NO SPECIFIC PROTECTION.

| Level                | Description  |
|----------------------|--|
| Top-level protection | Hikvision products at this level are equipped for use in areas where professional anti-corrosion protection is a must. Typical application scenarios include coastlines, docks, chemical plants, and more.   |
| Moderate protection  | Hikvision products at this level are equipped for use in areas with moderate anti-corrosion demands. Typical application scenarios include coastal areas about 2 kilometers (1.24 miles) away from coastlines, as well as areas affected by acid rain. |

|                        |   |
|------------------------|---|
| No specific protection | Hikvision products at this level are equipped for use in areas where no specific anti-corrosion protection is needed. |
|------------------------|---|

## Dimension



## Accessory



DS-1280ZJ-XS  
Junction Box

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Africa**  
T +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision Europe**  
T +31-23-55-42-770  
info.eu@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761

**Hikvision Middle East**  
T +971-4-8816086  
salesme@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Canada**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
potland@hikvision.com

**Hikvision Korea**  
T +82-31-731-8841  
sales.korea@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision UK**  
T +01628-902140  
support.uk@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com