


The Prolink logo features the word "PROLINK" in a bold, white, sans-serif font. A white, curved line arches over the letters "O" and "L", and another white, curved line arches under the letters "I" and "N".

PROLINK

A close-up photograph of a network switch or patch panel. The device is a light-colored metal rack-mountable unit. It features multiple rows of blue fiber optic ports. Numerous yellow fiber optic cables are plugged into these ports. The scene is dramatically lit with a strong blue light source from the left, creating a bright glow and casting deep shadows. The background is dark, making the illuminated components stand out. A white label with the text "FIO 12" is visible on the front panel of the device.






We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.

Powered by:  **PROLINK**

Discription




ProLink F/O JUMPER CORD ,LC -LC-MM DUPLEX – OM4 20M

Features

-  Small Size, High Precision.
-  Zirconia 1.25mm ceramics ferrule.
-  Low insertion Loss.
-  High Return Loss.
-  Duplex are Available.



Applications

-  Telecom and Datacom Equipment.
-  LAN/WAN
-  Device Terminals

Speciation's

Connectors type	LC-LC
Cable	OM4 Duplex 20M
Fiber Type	OM4 50/125
Cable Color	Fuchsia
insertion loss	≤0.25 dB
return loss	≥30dB
joint endurance	>1000Times
Operating Temperature	-40°C~+70°C
Storage Temperature	-25°C~+60°C
ROHS	Meet 2002/95/EC Requirement