


The Prolink logo features the word "PROLINK" in a bold, white, sans-serif font. A white, curved line arches over the letters "O" and "L", and another white, curved line arches under the letters "I" and "N".

PROLINK

A close-up photograph of a network switch or patch panel. The device is a light-colored metal rack-mountable unit. It features multiple rows of blue RJ45 ports and fiber optic ports. Several yellow fiber optic cables are plugged into the ports. A white label on the front of the unit reads "FIO 12 CUP". The lighting is dramatic, with a bright yellow and blue glow emanating from the cables and ports, creating a sense of high-tech connectivity.






We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.


Powered by:  **PROLINK**

Discription




ProLink F/O JUMPER CORD ,SC -SC-SM DUPLEX -3M

Features

-  Small Size, High Precision.
-  Zirconia 1.25mm ceramics ferrule.
-  Low insertion Loss.
-  High Return Loss.
-  Duplex are Available.



Applications

-  Telecom and Datacom Equipment.
-  LANWAN
-  Device Terminals

Speciations

Connectors type	SC-SC
Cable	SM Duplex 3.0 LSZH 3M
Fiber Type	SM 9/125
Cable Color	Yellow
insertion loss	-0.3 dB
return loss	≥45dB
joint endurance	> 1000Times
Operating Temperature	-40°C~+70°C
Storage Temperature	-25°C~+60°C
ROHS	Meet 2002/95/EC Requirement