


The Prolink logo features the word "PROLINK" in a bold, white, sans-serif font. A white, curved line arches over the letters "O" and "L", and another white, curved line arches under the letters "I" and "N".

# PROLINK

A close-up photograph of a network switch or patch panel. The device is a tan-colored metal rack-mountable unit. It features multiple rows of blue RJ45 ports and fiber optic ports. Several yellow fiber optic cables are plugged into the ports. A white label on the front of the unit reads "FIO 12 CUP". The lighting is dramatic, with a bright yellow light source creating a strong lens flare effect across the center of the image.

We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.

Powered by:  **PROLINK**





**Discerption**

ProLink Coupler SC MM-DUPLEX OM3

**Description**




Prolink Couplers have been designed for installation into Prolink fiber patch panels and termination boxes. Provide a robust and easy way to terminate.

**Features**

-  Small Size, High Precision.
-  Zirconia ceramics ferrule.
-  Low insertion Loss.
-  High Return Loss



**Applications**

-  Telecom and Datacom Equipment.
-  LAN/WAN
-  Device Terminals

**Speciation's**

Connectors type	SC
<b>Fiber Type</b>	OM3 50/125
<b>Coupler Color</b>	Turquoise
<b>Coupler Color</b>	turquoise
<b>Insertion loss</b>	0.1dB
<b>Return loss</b>	>20dB