


The Prolink logo features the word "PROLINK" in a bold, white, sans-serif font. A white, curved line arches over the letters "O" and "L", and another white, curved line arches under the letters "I" and "N".

PROLINK

A close-up, low-angle shot of a network switch or patch panel. The device is a tan-colored metal rack-mountable unit. It features multiple rows of blue RJ45 ports and fiber optic ports. Several yellow fiber optic cables are plugged into the ports, and a bright yellow light beam is directed at one of the ports. The background is dark, and the lighting is dramatic, highlighting the textures of the metal and plastic components.

We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.

Powered by: The Prolink logo, consisting of the word "PROLINK" in a bold, white, sans-serif font, with a white, curved line arching over the letters "O" and "L", and another white, curved line arching under the letters "I" and "N".





Discerption

ProLink Coupler LC MM-DUPLEX OM3

Description




Prolink Couplers have been designed for installation into Prolink fiber patch panels and termination boxes. Provide a robust and easy way to terminate.

Features

-  Small Size, High Precision.
-  Zirconia ceramics ferrule.
-  Low insertion Loss.
-  High Return Loss



Applications

-  Telecom and Datacom Equipment.
-  LAN/WAN
-  Device Terminals

Speciation's

Connectors type	LC
Fiber Type	OM3 50/125
Coupler Color	Turquoise
Coupler Color	turquoise
Insertion loss	0.1dB
Return loss	>20dB