



Schneider Electric EASY UPS BVS 500VA, Schuko outlet

BVS500I-GR

Product or component type	Uninterruptible power supply (UPS)
Battery type	Lead-acid battery
Topology	Line interactive
Quantity per set	Set of 1
Reset	Automatic reset
Range of product	Easy UPS 1Ph BVS Series

Complementary	
Type of installation	Indoor
Surge Energy	156 J
Type of signal	Stepped approximation to a sinewave
Protection device type	Surge protection device (SPD) Miniature circuit breaker (MCB) Fuse
Input voltage	230 V AC
Output voltage	230 V
IP degree of protection	IP20
Transfer time	6 ms typical : 10 ms maximum
Network frequency	4565 Hz
Power range	500 VA 300 W
Electrical connection	Input: 1 inlet Schuko CEE 7/P Output: 4 outlet Schuko CEE 7
Local signalling	Alarm, distinctive for low battery Alarm, continuous or intermittent tone for overload LED for battery status
Number of batteries	1
Charging time	8 h
Battery voltage	12 V
Battery capacity	4.5 Ah
Battery life	5 year(s)
Net weight	3.9 kg

Height	92.5 mm
Width	160.5 mm
Depth	305 mm
Farinanant	
Environment Relative humidity	090 %, non-condensing
Operating altitude	06561 ft
Ambient air temperature for	040 °C
operation	040 G
Product certifications	CE
Physical	
Mounting support	Wall
	Floor
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.901 kg
Package 1 Height	30.505 cm
Package 1 width	16.51 cm
Package 1 Length	9.246 cm
SCC14	10731304338441
Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Weight	17.78 kg
Package 2 Height	25 cm
Package 2 width	39 cm
Package 2 Length	58 cm
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Weight	230.41 kg
Package 3 Height	105 cm
Package 3 width	80 cm
Package 3 Length	120 cm
Office Constant at 199	
Offer Sustainability	REACh Declaration
REACh Regulation EU RoHS Directive	
LO NONS DIRECTIVE	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
	1

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

WEEE

Contractual warranty

Warranty	2 years