

Product datasheet

Specifications



APC Easy UPS BVX 700VA, 230V, AVR, Schuko Sockets

BVX700LI-GR

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Input voltage	230 V AC 1 phase
---------------	------------------

Output voltage	230 V AC 1 phase
----------------	------------------

Rated power in W	360 W
------------------	-------

Rated power in VA	700 VA
-------------------	--------

Plug standard	Schuko
---------------	--------

Nb of power socket outlets	2 Schuko
----------------------------	----------

Cable length	1.22 m
--------------	--------

Number of cables	1
------------------	---

Battery type	Lead-acid battery
--------------	-------------------

Provided equipment	User manual
--------------------	-------------

General

Max runtime	120 min
-------------	---------

Number of power module free slots	0
-----------------------------------	---

Number of power module filled slots	0
-------------------------------------	---

Redundant	No
-----------	----

UPS size	WS
----------	----

Physical

Colour	Black
--------	-------

Height	13.8 cm
--------	---------

Width	9.8 cm
-------	--------

Depth	31 cm
-------	-------

Net weight	4.2 kg
------------	--------

Mounting support	Floor
------------------	-------

Mounting preference	No preference
---------------------	---------------

Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto sensing
Input voltage limits	140...300 V 230 V AC
Cos phi	0.51

Output

Maximum configurable power in W	360 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sine wave
Full load runtime	00:00:01 360 W
Graph display	1
Half load runtime	00:06:00 180 W
Maximum configurable power in VA	700 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE CB
Standards	EN/IEC 62040-1 EN/IEC 62040-2 CE
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	12 V
Battery capacity	7.0 Ah

Battery life	2...3 year(s)
Extended runtime	0

Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Package 1 Weight	4.5 kg
Package 1 Height	22.2 cm
Package 1 width	14.2 cm
Package 1 Length	34.6 cm
SCC14	10731304404580

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------
