



Dell EMC PowerSwitch N1500 Series Switches

Extending enterprise features to small and mid-sized businesses

The N1500 switch series offers a power-efficient Gigabit Ethernet (GbE) network-access switching solution with integrated 10GbE uplinks. With high-performance capabilities and wire-speed performance, utilizing a non-blocking architecture to easily handle unexpected traffic loads, the switches offer simple management and scalability via an 40Gbps (full-duplex) high availability stacking architecture that allows management of up to four switches from a single IP address. An integrated 80PLUS-certified power supply and features such as Energy-Efficient Ethernet and short cable detection provide energy efficiency to help decrease power and cooling costs.

Modernize campus network architectures

Modernize campus network architectures with a power-efficient and resilient 1/10GbE switching solution with Power over Ethernet Plus (PoE+). Select N1500 models offer 24 or 48 ports of PoE+ to deliver clean power to network devices such as wireless access points (APs), Voice-over-IP (VoIP) handsets, video conferencing systems and security cameras.

Leverage familiar tools and practices

All N-Series switches include Dell EMC Networking OS6, designed for easier deployment, greater interoperability and a lower learning curve for network administrators. OS6 common command line interface (CLI) and graphic user interface (GUI) using a well-known command language gets skilled network administrators productive quickly. With USB auto-configuration, network administrators can rapidly deploy mirrored configurations to numerous devices by simply inserting a USB key.

Deploy with confidence at any scale

N1500 series switches help create performance assurance with a data rate up to 176Gbps (full duplex) and a forwarding rate up to 164Mpps. Scale easily by stacking with 10GbE ports. Switch stacks of up to 200 1GbE ports can be managed from a single screen using the highly available stacking architecture for high-density aggregation with seamless redundant availability. N-Series switches help provide certainty with a lifetime warranty that covers software upgrades, hardware repair or replacement, and optics and cables purchased with the switch.*

Hardware, performance and efficiency

- Up to 48 line-rate GbE RJ-45 ports and four integrated 10GbE SFP+ ports.
- Up to 48 ports of PoE+ with an optional external power supply.
- Up to 200 1GbE ports in a 4-unit stack for high-density, high-availability in IDFs, MDFs and wiring closets.
- Non-stop forwarding and fast failover in stack configurations.
- Energy-Efficient Ethernet and lower power PHYs reduce power to inactive ports and idle links, providing energy savings from the power cord to the port.
- Fresh Air compliance for operation in environments up to 113°F (45°C) helps reduce cooling costs in temperature-constrained deployments.

*Select Networking products carry a Lifetime Limited Warranty with Basic Hardware Service (repair or replacement) for life. Repair or replacement does not include troubleshooting, configuration, or other advanced service provided by Dell EMC ProSupport. For details, visit <https://www.dell.com/en-us/work/shop/networkingwarranty/cp/networkingwarranty>.

Deploying, configuring and managing

- USB auto-configuration rapidly deploys the switch without setting up complex TFTP configurations or sending technical staff to remote offices.
- Management via an intuitive and familiar CLI, embedded web server (GUI), SNMP-based management console application (including Dell EMC OpenManage Network Manager), Telnet or serial connection.
- Private VLAN extensions and Private VLAN Edge support.

Product	Description
N1500 series	N1524: 24x RJ45 10/100/1000Mb auto-sensing ports, 4x SFP+ ports, 1 integrated 40W PSU N1524P: 24x RJ45 10/100/1000Mb PoE+ (up to 30.8w) auto-sensing ports, 4x SFP+ ports, 1 integrated 600W PSU (requires C15 plug) N1548: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x SFP+ ports, 1 integrated 100W PSU N1548P: 48x RJ45 10/100/1000Mb PoE+ (up to 30.8w) auto-sensing ports, 4x SFP+ ports, 1 integrated 600W PSU (requires C15 plug)
Power cords	C13 to NEMA 5-15, 3M C13 to C14, 2M C15 to NEMA 5-15, 2M (C15 for POE N-Series only)
Power supplies (optional)	RPS720 external power supply for N1500 non-POE (720 watts): N1524 and N1548 (sold separately) MPS1000 external power supply for N1500 PoE+ switches (1000 watts): N1524P and N1548P (sold separately)
Optics (optional)	Transceiver, SFP, 1000BASE-T Transceiver, SFP, 1000BASE-SX, 850nm wavelength, up to 550m reach Transceiver, SFP, 1000BASE-LX, 1310nm wavelength, up to 10km reach Transceiver, SFP, 1000BASE-ZX, 1550nm wavelength, up to 80km reach Transceiver, SFP+, 10GbE, SR, 850nm wavelength, up to 300m reach Transceiver, SFP+, 10GbE, LR, 1310nm wavelength, up to 10km reach Transceiver, SFP+, 10GbE, ER, 1550nm wavelength, up to 40km reach
Cables (optional)	Dell Technologies Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct

Technical specifications

Hardware specifications

Physical

4 integrated front 10GbE SFP+ dedicated ports,
2 10GbE can be used as stacking ports
USB (Type A) port for configuration via USB flash drive
Auto-negotiation for speed and flow control
Auto MDI/MDIX, port mirroring
Flow-based port mirroring
Broadcast storm control
Energy-Efficient Ethernet per port settings
Redundant variable speed fans
Air flow: I/O to power supply
Integrated power supply: 40W AC (N1524), 100W AC (N1548), 600W AC (N1524P, N1548P)
RJ45 console port with RS232 signaling (RJ-45 to female DB-9 connector cable included)
Dual firmware images on-board
Switching engine model: Store and forward

Chassis

Size (1RU, H x W x D):
N1524 and N1548: 1.7 in x 17.3 in x 10.1 in (43.2 mm x 440.0 mm x 257.0 mm)
N1524P and N1548P: 1.7 in x 17.3 in x 15.2 in (43.2 mm x 440.0 mm x 387.0 mm)
Approximate weight: 6.6lbs/3kg (N1524), 12.8lbs/5.8kg (N1524P), 8.8lbs/4kg (N1548), 15.4lbs/7kg (N1548P)
Rack mounting kit with 2 mounting brackets, bolts and cage nuts

Environmental

Power supply efficiency: 80% or better in all operating modes
Max. thermal output (BTU/hr): 103.1 (N1524), 2972 (N1524P), 152.2 (N1548), 5824.3 (N1548P)
Power consumption max (watts): 30.2 (N1524), 871 (N1524P), 44.6 (N1548), 1704 (N1548P)
Operating temperature: 32° to 113°F (0° to 45°C)
Operating humidity: 95%
Storage temperature: -40° to 149°F (-40° to 65°C)
Storage relative humidity: 85%

Performance

MAC addresses: 16K
Static routes: 256 (IPv4)/128 (IPv6)
Dynamic routes: 256 (IPv4)
Switch fabric capacity: 128Gbps (N1524 and N1524P) (full duplex); 176Gbps (N1548 and N1548P)
Forwarding rate: 128Mpps (86 Gbps) N1524 and N1524P
164Mpps (110 Gbps) N1548 and N1548P
Link aggregation: 64 LAG groups, 144 dynamic ports per stack, 8 member ports per LAG
Priority queues per port: 8
Line-rate Layer 2 switching: All (non-blocking)
Line-rate Layer 3 routing: All (non-blocking)
Flash memory: 256MB
Packet buffer memory: 1.5MB
CPU memory: 1GB
RIP routing interfaces: 128
VLAN routing interfaces: 128
VLANs supported: 512

Protocol-based VLANs: Supported
ARP entries: 2,048 (IPv4)/512 (IPv6)
NDP entries: 400
Access control lists (ACL): Supported
MAC and IP-based ACLs: Supported
Time-controlled ACLs: Supported
Max number of ACLs: 100
Max ACL rules system-wide: 2,048
Max rules per ACL: 1,023
Max ACL rules per interface (IPv4): 1,023 (ingress), 1,023 (egress)
Max ACL rules per interface (IPv6): 512 (ingress), 509 (egress)
Max VLAN interfaces with ACLs applied: 24

IEEE compliance

802.1AB LLDP
Dell Voice VLAN
Dell ISDP (inter-operates with devices running CDP)
802.1D Bridging, Spanning Tree
802.1p Ethernet Priority (User Provisioning and Mapping)
Dell Adjustable WRR and Strict Queue Scheduling
802.1Q VLAN Tagging, Double VLAN Tagging, GVRP
802.1S Multiple Spanning Tree (MSTP)
802.1v Protocol-based VLANs
802.1W Rapid Spanning Tree (RSTP)
Dell RSTP-Per VLAN (compatible with Cisco's RPVST+)
Dell Spanning tree optional features: STP root guard, BPDU guard, BPDU filtering
802.1X Network Access Control, Auto VLAN

Technical specifications

802.2	Logical Link Control	1213	MIB-II	4521	LDAP Extensions
802.3	10BASE-T	1215	SNMP Traps	4716	SECSH Public Key File Format
802.3ab	Gigabit Ethernet (1000BASE-T)	1286	Bridge MIB	5246	TLS v1.2
802.3ac	Frame Extensions for VLAN Tagging	1442	SMIv2	6101	SSL
802.3ad	Link Aggregation with LACP	1451	Manager-to-Manager MIB	Dell	Enterprise MIB supporting routing features draft-ietf-hubmib-etherif-mib-v3-00.txt (Obsoletes RFC 2665)
802.3ae	10 Gigabit Ethernet (10GBASE-X)	1492	TACACS+	Dell	LAG MIB Support for 802.3ad Functionality (Draft version 1.3 draft 5)
802.3at	PoE+ (N1524P and N1548P)	1493	Managed Objects for Bridges MIB	Dell	802.1x Monitor Mode
802.3AX	LAG Load Balancing	1573	Evolution of Interfaces	Dell	Custom Login Banners
802.3az	Energy Efficient Ethernet (EEE)	1612	DNS Resolver MIB Extensions	Dell	Dynamic ARP Inspection
802.3u	Fast Ethernet (100BASE-TX) on Management Ports	1643	Ethernet-like MIB	Dell	IP Address Filtering
802.3x	Flow Control	1757	RMON MIB	Dell	Tiered Authentication
802.3z	Gigabit Ethernet (1000BASE-X)	1867	HTML/2.0 Forms with File Upload Extensions	Dell	RSPAN
ANSI	LLDP-MED (TIA-1057)	1901	Community-based SNMPv2	Dell	OpenFlow 1.3
MTU	9,216 bytes	1907	SNMPv2 MIB	Dell	Python Scripting
		1908	Coexistence Between SNMPv1/v2	Dell	Support Assist
		2011	IP MIB	HiveManager NG	
		2012	TCP MIB		
		2013	UDP MIB		
		2068	HTTP/1.1		
		2096	IP Forwarding Table MIB		
		2233	Interfaces Group using SMIv2		
		2246	TLS v1		
		2271	SNMP Framework MIB		
		2295	Transport Content Negotiation		
		2296	Remote Variant Selection		
		2576	Coexistence Between SNMPv1/v2/v3		
		2578	SMIv2		
		2579	Textual Conventions for SMIv2		
		2580	Conformance Statements for SMIv2		
		2613	RMON MIB		
		2618	RADIUS Authentication MIB		
		2620	RADIUS Accounting MIB		
		2665	Ethernet-like Interfaces MIB		
		2674	Extended Bridge MIB		
		2737	ENTITY MIB		
		2818	HTTP over TLS		
		2819	RMON MIB (groups 1, 2, 3, 9)		
		2863	Interfaces MIB		
		2865	RADIUS		
		2866	RADIUS Accounting		
		2868	RADIUS Attributes for Tunnel Prot.		
		2869	RADIUS Extensions		
		3410	Internet Standard Mgmt. Framework		
		3411	SNMP Management Framework		
		3412	Message Processing and Dispatching		
		3413	SNMP Applications		
		3414	User-based security model		
		3415	View-based control model		
		3416	SNMPv2		
		3418	SNMP MIB		
		3577	RMON MIB		
		3580	802.1X with RADIUS		
		3737	Registry of RMOM MIB		
		4086	Randomness Requirements		
		4113	UDP MIB		
		4251	SSHv2 Protocol		
		4252	SSHv2 Authentication		
		4253	SSHv2 Transport		
		4254	SSHv2 Connection Protocol		
		4419	SSHv2 Transport Layer Protocol		

General Internet protocols

General Internet protocols are supported. For a detailed list, please contact your Dell Technologies representative.

General IPv4 protocols

General IPv4 protocols are supported. For a detailed list, please contact your Dell Technologies representative.

General IPv6 protocols

General IPv6 protocols are supported. For a detailed list, please contact your Dell Technologies representative.

Layer 3 functionality

1058	RIPv1
2082	RIP-2 MD5 Auth
1724	RIPv2 MIB Extension
2453	RIPv2

Multicast

2932	IPv4 MIB
4541	IGMP v1/v2/v3 Snooping and Querier
IEEE 802.1ag draft 8.1-	Connectivity Fault Management

Quality of service

2474	DiffServ Field
Dell	Flow Based QoS
2475	DiffServ Architecture Services Mode
2597	Assured Fwd PHB (IPv4/IPv6)
Dell	L4 Trusted Mode
Dell	Port Based QoS (TCP/UDP) Services Mode
Dell	UDLD

Network Management and Security

1155	SMIv1
1157	SNMPv1
1212	Concise MIB Definitions

Regulatory, environment and other compliance

Safety and emissions

Australia/New Zealand: ACMA RCM Class A
 Canada: ICES Class A; cUL
 China: CCC Class A; NAL
 Europe: CE Class A
 Japan: VCCI Class A
 USA: FCC Class A; NRTL UL; FDA 21 CFR 1040.10 and 1040.11
 Eurasia Customs Union: EAC
 Germany: GS mark
 Product meets EMC and safety standards in many countries inclusive of USA, Canada, EU, Japan, China.
 For more country-specific regulatory information and approvals, please see your Dell Technologies representative.

RoHS

Product meets RoHS compliance standards in many countries inclusive of USA, EU, China, and India. For more country-specific RoHS compliance information, please see your Dell Technologies representative.
 EU WEEE
 EU Battery Directive
 REACH

Energy

Japan: JEL
 Certifications (available or coming soon)
 Available with US Trade Agreements Act (TAA) compliance.
 N-Series products have the necessary features to support a PCI-compliant network topology.

IT Lifecycle Services for Networking

Experts, insights and ease

Our highly trained experts, with innovative tools and proven processes, help you transform your IT investments into strategic advantages.



Plan & Design

Let us analyze your multivendor environment and deliver a comprehensive report and action plan to build upon the existing network and improve performance.



Deploy & Integrate

Get new wired or wireless network technology installed and configured with ProDeploy. Reduce costs, save time, and get up and running fast.



Educate

Ensure your staff builds the right skills for long-term success. Get certified on Dell EMC Networking technology and learn how to increase performance and optimize infrastructure.



Manage & Support

Gain access to technical experts and quickly resolve multivendor networking challenges with ProSupport. Spend less time resolving network issues and more time innovating.



Optimize


Maximize performance for dynamic IT environments with Dell EMC Optimize. Benefit from in-depth predictive analysis, remote monitoring and a dedicated systems analyst for your network.



Retire

We can help you resell or retire excess hardware while meeting local regulatory guidelines and acting in an environmentally responsible way.

Learn more at DellTechnologies.com/Services



[Learn more](#) about Dell EMC Networking solutions



[Contact](#) a Dell Technologies Expert



[View more](#) resources



Join the conversation with [@DellNetworking](#)